



روغن کمپرسور اسکرو

**KIMIYA ATLAS GROUP**

## **DAYTO CORENA S2R LUBRICANT**

### **TYPICAL DATA SHEET**

Properties	Test Method	Result	Result	Result
Grade	-	46	55	68
Kin. Vis. @ 40 °C, cSt	ASTM D-445	46 cSt	56 cSt	68 cSt
Viscosity Index	ASTM D-2270	110	107	106
Density @15°C, g/cm <sup>3</sup>	ASTM D-1298	0.86	0.87	0.87
Flash Point, °C	ASTM D-92	235	240	245
Pour Point , °C	ASTM D-97	-33	-30	-30
Total Acid Number mgKOH/g	ASTM D-664	0.25	0.3	0.3
Water sep@54 °C	ASTM D-1401	15	20	25
Foaming Behavior	ASTM D-892			
Seq.II		30/0	20/0	20/0
FZG Test	CEC-L-07-A-85	11	11	11
NAS Class	NAS 1638	9	9	9
Corrosion Effect On Copper	ASTM D-130	1a	1a	1a
Corrosion Effect On Steel	ASTM D-665	Pass	Pass	Pass
PRVOT	ASTM D-2272	650	600	550
Air Separation Capacity	ASTM D-3427	2.5 min	3.5 min	4.5 min