



روغن کمپرسور اسکرو

KIMIYA ATLAS GROUP

DAYTO CORENA S3R LUBRICANT

TYPICAL DATA SHEET

Properties	Test Method	Result	Result	Result
Grade	-	46	55	68
Kin. Vis. @ 40 °C, cSt	ASTM D-445	47 cSt	54 cSt	67 cSt
Viscosity Index	ASTM D-2270	125	120	119
Density @15°C, g/cm ³	ASTM D-1298	0.85	0.86	0.865
Flash Point, °C	ASTM D-92	240	245	250
Pour Point , °C	ASTM D-97	-36	-33	-30
Total Acid Number mgKOH/g	ASTM D-664	0.25	0.3	0.3
Water sep@54 °C - minutes	ASTM D-1401	15	20	22
Foaming Behavior Seq.II	ASTM D-892	20/0	15/0	15/0
FZG Test	CEC-L-07-A-85	12	12	12
NAS Class	NAS 1638	9	9	9
Corrosion Effect On Copper	ASTM D-130	1a	1a	1a
Corrosion Effect On Steel	ASTM D-665	Pass	Pass	Pass
PRVOT	ASTM D-2272	700	650	600
Air Separation Capacity	ASTM D-3427	2.5 min	3.2 min	4 min